

All dimensions in mm	If in doubt - ask	©

Customer Information Sheet

Tape Details


Scale 11:2







Specifications:
Material:
Beryllium Copper
Finish (See order code):
45 = Gold flash over Nickel
25 = 0.25µm Min. Gold over Nickel
Electrical:
Current Rating = 6.0A
Contact Resistance = 0.15mΩ Max.
Environmental:
Operating Temperature = -40°C to +180°C

Component Details





Reel Details



Order Code:

S70-3XX00XXXXR

Size:
DIM 'A' = Diameter X.Xmm
DIM 'B' = Thickness 0.XXmm
Finish
45 - Gold Flash over Nickel
25 - 0.25µm Gold over Nickel

Table 1: Part Numbers & Dimensions

Part No.	ØDIM 'A'	DIM 'B' ±0.05	Qty Per Reel
S70-3200020XXR	2.00	0.20	7000
S70-3200050XXR	2.00	0.50	7000
S70-3320020XXR	3.20	0.20	2000
S70-3320050XXR	3.20	0.50	7000

-	-	-	-
Initials	Rev.	Date	CO
RA	1	08.05.26	38728

Notes:
1. Cumulative tolerance over 10 pitches = ±0.2mm.
2. Product to be tape and reeled in general accordance with EIA-481.
3. Care is to be taken when selecting aperture size, stencil thickness, and solder paste to avoid float or solder creeping onto the top surface of the contact.

HARWIN
www.harwin.com

This drawing and any information or descriptive matter set out hereon are confidential and copyright property of the Harwin group and must not be disclosed, loaned, copied or used for manufacturing, tendering or for any other purpose without their written permission.

TOLERANCES
X. = ±0.50mm
X.X = ±0.30mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
Angles = ±5°
Unless stated

Third angle projection

Sheet scale: 30:1
Do not scale
Sheet size: A3

MATERIAL: See Above

FINISH: See Above

Title: SMT Circular Contact Pads

Drawing number: **S70-3XX00XXXXR**

SHT 2 OF 2