Customer Information DRAWING No.: M80-5T11222M3-04-331-00-000 IF IN DOUBT - ASK NOT TO SCALE THIRD ANGLE PROJECTION ALL DIMENSIONS IN mm SPECIFICATIONS: MATERIAL: MOULDING: GLASS FILLED PPS, UL94V-O, BLACK SIGNAL CONTACT: PHOSPHOR BRONZE -38.0-POWER CONTACT: COPPER ALLOY BOARD-MOUNT JACKSCREW, NUT: STAINLESS STEEL FINISH: SIGNAL CONTACT: 5.60-- 4.00 TYP MAX75µ GOLD ON CONTACT AREA, CONTACT No. 1-2.00 3µ 90/10 TIN/LEAD ON TAILS POWER CONTACT: GOLD **ELECTRICAL:** WORKING VOLTAGE = 800V AC/DC VOLTAGE PROOF = 1200V AC/DC INSULATION RESISTANCE = $100M\Omega$ MIN MAX SIGNAL CONTACT: CURRENT RATING AT 25°C = 3.0A MAX CURRENT RATING AT 85°C = 2.2A MAX CONTACT RESISTANCE = $25m\Omega$ MAX POWER CONTACT: 0.50 SECTION X-X CONTACT RESISTANCE 6mΩ MAX 2.00 TYP 3.00 CURRENT RATING = 20A MAX -10.00 MECHANICAL: 3.50 -12.00 DURABILITY = 500 OPERATIONS -2 x M2x0.4 SIGNAL CONTACT: INSERTION FORCE = 2.0N MAX WITHDRAWAL FORCE = 0.2N MIN POWER CONTACT: INSERTION FORCE = 8N MAX SECTION Y-Y WITHDRAWAL FORCE = 0.5N MIN **ENVIRONMENTAL:** TEMPERATURE RANGE = -55°C TO +125°C PACKING: FOR COMPLETE SPECIFICATION SEE COMPONENT SPECIFICATION COO5XX (LATEST ISSUE) (3.3)(5.0)NOTE: I. CONNECTORS ARE SUPPLIED WITH 3.00 NUTS LOOSE. 4 x Ø l . 50 — — 12 x Ø0.50 2 x Ø 4.00 -33.00-12.00 10.00-25.09.17 13269 2.00 TYP - 4.50 4.00 TYP DATE C/NOTE APPROVED: F. MCGOWAN CHECKED: M. PLESTED 2.00 DRAWN: B. M. KENT COMPLETE ASSEMBLY SHOWN FOR ILLUSTRATION ONLY CUSTOMER REF.: $4 \times \emptyset 1.65 \pm 0.05$ ASSEMBLY DRG: $12 \times \emptyset 0.70 \pm 0.05$ $2 \times \emptyset 2.25 \pm 0.05$ RECOMMENDED PCB LAYOUT THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION. TOLERANCES MATERIAL: JACKSCREW DATAMATE X. = ±1mm MIXED TECHNOLOGY VERTICAL SEE ABOVE $X.X = \pm 0.50$ mm PC TAIL MALE ASSEMBLY $X.XX = \pm 0.10$ mm $X.XXX = \pm 0.01$ mm DRAWING NUMBER: FINISH: SEE ABOVE www.harwin.com ANGLES = ±5° M80-5T11222M3-04-331-00-000 CoF, technical@harwin.com UNLESS STATED S/AREA: