

Material Composition for M55-605XX42R

Product Information	
Part Number:	M55-605XX42R
Part Description:	1.27mm pitch Socket
Part Weight (g):	(0.0247 * XX) + 0.127

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact - Phosphor Bronze	0.0132 * XX	5%	Copper	7440-50-8
	0.000885 * XX	1%	Tin	7440-31-5
	0.000027 * XX	0.5%	Phosphorus	7723-14-0
	0	(0.000028 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.000014 * XX)g max	Iron (impurity only)	7439-89-6
Contact - Plating	0	(0.000007 * XX)g max	Lead (impurity only)	7439-92-1
	0	(0.000071 * XX)g max	Other Impurities	
	0.000275 * XX	10%	Nickel	7440-02-0
	0.000046 * XX	10%	Tin	7440-31-5
	0.000003 * XX	10%	Gold	7440-57-5
Retainers - Brass				
	0.0336	5%	Copper	7440-50-8
	0.0144	1%	Zinc	7440-66-6
	0	0.00001g max	Aluminium (impurity only)	7429-90-5
	0	0.000144g max	Nickel (impurity only)	7440-02-0
Retainers - Plating	0	0.000048g max	Tin (impurity only)	7440-31-5
	0	0.000024g max	Iron (impurity only)	7439-89-6
	0	0.000034g max	Lead (impurity only)	7439-92-1
	0	0.000048g max	Other Impurities	
	0.000594	10%	Nickel	7440-02-0
Moulding (total weight)	0.00123	10%	Tin	7440-31-5
	(0.0103 * XX) + 0.077	6%	33% GF LCP	
	(0.0069 * XX) + 0.0516	6%	Liquid Crystal Polymer	
	(0.0034 * XX) + 0.0254	6%	Glass Fibre	65997-17-3
Does not contain:			Other Brominated Flame Retardants	
			Antimony	

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
compliance@harwin.com

On behalf of:

HARWIN