

Material Declaration for M80-4000000F1-XX-305-00-000

Product Information	
Part Number:	M80-4000000F1-XX-305-00-000
Part Description:	Datamate Mix-Tek Female cable
Part Weight (g):	(0.743 * XX) + 0.724
Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	Gold over Nickel/Copper
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Coax Contact Shell - Brass	0.104 * XX	2%	Copper	7440-50-8
	0.0702 * XX	1%	Zinc	7440-66-6
	0.0054 * XX	0.5%	Lead	7439-92-1
	0	(0.00054 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.00054 * XX)g max	Tin (impurity only)	7440-31-5
Coax Contact Shell - Plating	0	(0.000054 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.00009 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.00036 * XX)g max	Other Impurities	
	0.00103 * XX	5%	Gold	7440-57-5
	0.00254 * XX	10%	Nickel	7440-02-0
Coax Contact Sleeve - Beryllium Copper	0.00212 * XX	10%	Copper	7440-50-8
	0.0248 * XX	2%	Copper	7440-50-8
	0.000101 * XX	0.4%	Beryllium	7440-41-7
	0.000456 * XX	0.8%	Nickel	7440-02-0
	0	(0.000076 * XX)g max	Cobalt (impurity only)	7440-48-4
Coax Contact Sleeve - Plating	0	(0.000025 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000127 * XX)g max	Other Impurities	
	0.000429 * XX	10%	Nickel	7440-02-0
	0.0347 * XX	5%	PTFE	9002-84-0
	0.0682 * XX	2%	Copper	7440-50-8
Coax Crimp Sleeve - Brass	0.0459 * XX	1%	Zinc	7440-66-6
	0.00353 * XX	0.5%	Lead	7439-92-1
	0	(0.000035 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000035 * XX)g max	Tin (impurity only)	7440-31-5
	0	(0.000035 * XX)g max	Nickel (impurity only)	7440-02-0
Coax Crimp Sleeve - Plating	0	(0.000059 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000235 * XX)g max	Other Impurities	
	0.000491 * XX	5%	Gold	7440-57-5
	0.00121 * XX	10%	Nickel	7440-02-0
	0.00101 * XX	10%	Copper	7440-50-8
Coax Inner Contact - Beryllium Copper	0.0199 * XX	1%	Copper	7440-50-8
	0.000387 * XX	0.2%	Beryllium	7440-41-7
	0.000081 * XX	0.5%	Lead	7439-92-1
	0	(0.000061 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.000061 * XX)g max	Cobalt (impurity only)	7440-48-4
Coax Inner Contact - plating	0	(0.000041 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000041 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000041 * XX)g max	Silicon (impurity only)	7440-21-3
	0	(0.000102 * XX)g max	Other Impurities	
	0.000604 * XX	5%	Gold	7440-57-5
Jackscrew Circlips - Stainless Steel	0.000493 * XX	10%	Nickel	7440-02-0
	0.0164	10%	Iron	7439-89-6
	0.0033	4%	Chromium (Metallic)	7440-47-3
	0.0002	4%	Nickel	7440-02-0
	0.000078	0.8%	Copper	7440-50-8
Jackscrew Bolts - Stainless Steel	0.000004	0.5%	Sulphur	7704-34-9
	0	0.000078g max	Carbon (impurity only)	7440-44-0
	0	0.0002g max	Silicon (impurity only)	7440-21-3
	0	0.0003g max	Manganese (impurity only)	7439-96-5
	0	0.000008g max	Phosphorus (impurity only)	7723-14-0
Moulding (total weight)	0	0.00021g max	Molybdenum (impurity only)	7439-98-7
	0	0.00004g max	Niobium (impurity only)	7440-03-1
	0	0.00002g max	Titanium (impurity only)	7440-32-6
	0.4	10%	Iron	7439-89-6
	0.099	4%	Chromium (Metallic)	7440-47-3
Containing:	0.0495	4%	Nickel	7440-02-0
	0.00385	0.8%	Copper	7440-50-8
	0.00137	0.5%	Sulphur	7704-34-9
	0	0.00066g max	Carbon (impurity only)	7440-44-0
	0	0.0055g max	Silicon (impurity only)	7440-21-3
Does not contain:	0	0.011g max	Manganese (impurity only)	7439-96-5
	0	0.00033g max	Phosphorus (impurity only)	7723-14-0
	0	0.0055g max	Molybdenum (impurity only)	7439-98-7
	0	0.0011g max	Niobium (impurity only)	7440-03-1
	0	0.00055g max	Titanium (impurity only)	7440-32-6
Other Brominated Flame Retardants				
Moulding (total weight)				
Containing:				
(0.123 * XX) + 0.15				
(0.0861 * XX) + 0.105				
(0.0369 * XX) + 0.045				
Does not contain:				
Antimony				
30% Glass-Filled PPS				
PPS				
30% Glass Fibre				

Prepared by: *M. J. Perry*

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
complianceteam@harwin.com

On behalf of:

HARWIN