

## Material Declaration for M80-532XXXX

Product Information	
Part Number:	M80-532XX05
Part Description:	2mm Horiz Datamate
Part Weight (g):	(0.048 * XX) + 0.63

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Brass	0.0156 * XX	10%	Copper	7440-50-8
	0.00918 * XX	10%	Zinc	7440-66-6
	0	(0.000025 * XX)g max	Lead (impurity only)	7439-92-1
	0	(0.000025 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000025 * XX)g max	Tin (impurity only)	7440-31-5
	0	(0.000074 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.000012 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000025 * XX)g max	Other Impurities	
Contacts - Plating	0.000323 * XX	5%	Gold	7440-57-5
	0.000252 * XX	10%	Nickel	7440-02-0
Jackscrews - Stainless Steel	0.233	10%	Iron	7439-89-6
	0.059	4%	Chromium (Metallic)	7440-47-3
	0.0295	4%	Nickel	7440-02-0
	0.00082	0.5%	Sulphur	7704-34-9
	0	0.000262g max	Carbon (impurity only)	7440-44-0
	0	0.00328g max	Silicon (impurity only)	7440-21-3
	0	0.00655g max	Manganese (impurity only)	7439-96-5
	0	0.000148g max	Phosphorus (impurity only)	7723-14-0
	0	0.00197g max	Molybdenum (impurity only)	7439-98-7
	0	0.00036g max	Nitrogen (impurity only)	7727-37-9
	0	0.00524g max	Copper (impurity only)	7440-50-8
Moulding (total weight)	(0.0226 * XX) + 0.308	10%	30% Glass-Filled PPS	
Containing:	(0.0158 * XX) + 0.216	10%	PPS	26125-40-6
	(0.00678 * XX) + 0.0924	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	

## Material Declaration for M80-532XXXX

Product Information	
Part Number:	M80-532XX22
Part Description:	2mm Horiz Datamate
Part Weight (g):	(0.0479 * XX) + 0.63

Process Data	
Peak Reflow (Deg. C)	235°C for 5 seconds
Termination Finish	Tin/Lead over Nickel
RoHS Compliant? (Y/N)	No

Note: RoHS compliant by threshold values, lead intentionally added, not recommended for Lead-Free Soldering.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Brass	0.0156 * XX	10%	Copper	7440-50-8
	0.00918 * XX	10%	Zinc	7440-66-6
	0	(0.000025 * XX)g max	Lead (impurity only)	7439-92-1
	0	(0.000025 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000025 * XX)g max	Tin (impurity only)	7440-31-5
	0	(0.000074 * XX)g max	Nickel (impurity only)	7440-02-0
Contacts - Plating	0	(0.000012 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000025 * XX)g max	Other Impurities	
	0.000096 * XX	5%	Gold	7440-57-5
	0.000114 * XX	5%	Tin	7440-31-5
	0.00002 * XX	5%	Lead	7439-92-1
Jackscrews - Stainless Steel	0.000252 * XX	10%	Nickel	7440-02-0
	0.233	10%	Iron	7439-89-6
	0.059	4%	Chromium (Metallic)	7440-47-3
	0.0295	4%	Nickel	7440-02-0
	0.00082	0.5%	Sulphur	7704-34-9
	0	0.000262g max	Carbon (impurity only)	7440-44-0
	0	0.00328g max	Silicon (impurity only)	7440-21-3
	0	0.00655g max	Manganese (impurity only)	7439-96-5
	0	0.000148g max	Phosphorus (impurity only)	7723-14-0
	0	0.00197g max	Molybdenum (impurity only)	7439-98-7
Moulding (total weight)	0	0.00036g max	Nitrogen (impurity only)	7727-37-9
	0	0.00524g max	Copper (impurity only)	7440-50-8
	(0.0226 * XX) + 0.308	10%	30% Glass-Filled PPS	
	(0.0158 * XX) + 0.216	10%	PPS	26125-40-6
Containing:	(0.00678 * XX) + 0.0924	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	

# Material Declaration for M80-532XXXX

Product Information	
Part Number:	M80-532XX42
Part Description:	2mm Horiz Datamate
Part Weight (g):	(0.0479 * XX) + 0.63

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Brass	0.0156 * XX	10%	Copper	7440-50-8
	0.00918 * XX	10%	Zinc	7440-66-6
	0	(0.000025 * XX)g max	Lead (impurity only)	7439-92-1
	0	(0.000025 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000025 * XX)g max	Tin (impurity only)	7440-31-5
	0	(0.000074 * XX)g max	Nickel (impurity only)	7440-02-0
Contacts - Plating	0	(0.000012 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000025 * XX)g max	Other Impurities	
	0.000096 * XX	5%	Gold	7440-57-5
	0.000127 * XX	5%	Tin	7440-31-5
Jackscrews - Stainless Steel	0.000252 * XX	10%	Nickel	7440-02-0
	0.233	10%	Iron	7439-89-6
	0.059	4%	Chromium (Metallic)	7440-47-3
	0.0295	4%	Nickel	7440-02-0
	0.00082	0.5%	Sulphur	7704-34-9
	0	0.000262g max	Carbon (impurity only)	7440-44-0
	0	0.00328g max	Silicon (impurity only)	7440-21-3
	0	0.00655g max	Manganese (impurity only)	7439-96-5
	0	0.000148g max	Phosphorus (impurity only)	7723-14-0
	0	0.00197g max	Molybdenum (impurity only)	7439-98-7
Moulding (total weight)	0	0.00036g max	Nitrogen (impurity only)	7727-37-9
	0	0.00524g max	Copper (impurity only)	7440-50-8
	(0.0226 * XX) + 0.308	10%	30% Glass-Filled PPS	
	Containing:	(0.0158 * XX) + 0.216	10%	PPS
Does not contain:	(0.00678 * XX) + 0.0924	10%	30% Glass Fibre	65997-17-3
			Antimony	
			Other Brominated Flame Retardants	

Prepared by: *M. J. Perry*

Martin J Perry, BSc(Eng) MSc CEng MIET  
Compliance Specialist  
ComplianceTeam@harwin.co.uk

On behalf of:

