

Material Declaration for G125-FC3XX05L0-YYYYL

Product Information	
Part Number:	G125-FC3XX05L0-YYYYL
Part Description:	Female Crimped Conn. with 30AWG Wires
Part Weight (g):	(0.031 * XX) + (0.00123 * XX * YYYY) + 0.649

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	Gold
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Beryllium Copper	0.0134 * XX	1%	Copper	7440-50-8
	0.00026 * XX	0.5%	Beryllium	7440-41-7
	0.00055 * XX	0.5%	Lead	7439-92-1
	0	(0.000041 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.000027 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000027 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000041 * XX)g max	Cobalt (impurity only)	7440-48-4
	0	(0.000027 * XX)g max	Silicon (impurity only)	7440-21-3
	0	(0.000068 * XX)g max	Other Impurities	
Contacts - Plating	0.000102 * XX	5%	Gold	7440-57-5
	0.000375 * XX	10%	Nickel	7440-02-0
Moulding (total weight)	(0.0124 * XX) + 0.0378	5%	30% GF Nylon 4T	
Containing:	(0.00694 * XX) + 0.0212	5%	Nylon 4T	103945-40-0
	(0.00372 * XX) + 0.0113	5%	30% Glass Fibre	65997-17-3
	(0.00155 * XX) + 0.00473	5%	Organic phosphorus compound	-
	(0.000186 * XX) + 0.000567	5%	Other Additives	-
Does not contain:			Antimony	
			Other Brominated Flame Retardants	
			Red Phosphorus	
Wire	0.000312 * XX * YYYY	10%	Copper	7440-50-8
Wire - Plating	0.000037 * XX * YYYY	10%	Silver	7440-22-4
Wire - Insulation	0.00088 * XX * YYYY	10%	PTFE	9002-84-0

Prepared by:

M. J. Perry

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of:

HARWIN